

SOUTH CUMBRIA RIVERS TRUST UK and Ireland Lakes Conference


Challenges of restoring natural function, improving water quality and lake hydrology. An example from Elterwater, Cumbria



Elterwater

- Within the World Heritage Lake District
- A Site of Special Scientific Interest due to its nationally important lake edge vegetation communities
- Lake itself largely un-disturbed by tourism







Overview:

- Elterwater's inner basin received the discharge from Elterwater sewerage works from 1974 – 1999
- Residual phosphate residues in the sediment have led to algal blooms in inner and middle basin
- Residence time is estimated >50 days
- SSSI is 'un-favorable declining'
- Other impacts include physical modifications to the inflows of Great Langdale Beck and Little Langdale Beck which bypassed middle basin.



Aims & Objectives:

- Reduce P levels to 15μg/I: SSSI favourable condition & WFD standard for 'good'. (In 2012 results were 19-23μg).
- Reduce the residence time in inner and middle basins
- Reduce the effects of stratification
- Return natural processes to the system







Steps taken so far:



- Feasibility study to assess options. Solution identified and funded by UU under the National Environment Programme.
- Installed a pipeline to transfer clean well-oxygenated water to the inner basin
- Re-connected Little Langdale beck to middle basin
- Created shallow scrapes to facilitate reconnection of Great Langdale beck to middle basin
- Removal of INNS (Japanese knotweed, Himalayan balsam, skunk cabbage all present)



Timeline of activity

10 years of restoration work.



2012: APEM Report & options scoping

2015 - 2016:

Detailed water quality monitoring, preintervention

2017: Initial Elterwater completion report submitted to United Utilities

2018: Eltermere Inn connected to mains sewerage

2021: Reconnection of **Great Langdale** Beck to middle basin











2016: Re-connection

of Little Langdale

beck to middle basin















2013: Elterwater Remediation Strategy Developed

2016: Installation of transfer pipeline from Great Langdale Beck

2017: Established of monthly water quality monitoring by SCRT

2018 - 2021: PhD study and further research

2019: Fish screen modified to reduce 'blinding' and increase potential water transfer

2022: Extension to temporary planning permission for the pipeline and proposed change in hands of flow from Q85 to Q90.

Options review:

APEM 2012

(Sites 9 & 10). Less effective (moderate) for diffuse sources but can reduce diffuse sediment source 'hot spots' Sediment Nutrient remove 90% of lock up sediment P for up to 10 years. Nutrient lock up sediment P for up to 10 years. No adverse impacts predicted. Likely to assist with aiming to achieve WFD compliance. Potentially adverse response from landowners/resi dents affected by improvement notices/enforce ment. Potentially adverse response from landowners/resi dents affected by improvement notices/enforce ment. Uncertainty of high epending application may on sediment depth treated. Sediment Nutrient remove 90% of lock up sediment P for up to 10 years. OP from the water column, and claimed to lock up sediment P for up to 10 years. OE with aiming to achieve WFD compliance. OP is taken up quickly and sediment P is locked up timmediately. OC community if early early early engagement sought. Potentially adverse from adding adverse from adding concentration of foreign assuming high expending and residents may incur costs. Potentially adverse response from landowners/resi dents affected by improvement notices/enforce ment. Uncertainty of high epending application may on sediment depth treated. Stakeholder acceptance could be compromised if viewed as a sticking plaster option rather than tackling plaster option rather than tac	Management Option	Nutrient Reduction Effectiveness	Probability of Success	Speed of Ecosystem Response	Environmental Impact	Community/ Social Impact	CAPEX	OPEX	Sustainability
Sediment Nutrient remove 90% of Inactivation Note and claimed to lock up sediment P for up to 10 years. Note and the sediment P for up to 10 years. Note and the sediment P for up to 10 years. Sediment Nutrient remove 90% of the lock up sediment P for up to 10 years. Note and the sediment P for up to 10 years. Sediment Nutrient remove 90% of the lock up sediment P for up to 10 years. Note and the sediment P for up to 10 years. Sediment Nutrient remove 90% of the lock up sediment P for up to 10 years. Note and the sediment P for up to 10 years. Sediment Nutrient remove 90% of the lock up sediment P for up to 10 years. Note and the sediment P is locked up immediately. No adverse impacts predicted. Likely to assist with aiming to achieve WFD compliance. Note and the sediment P is locked up immediately. No adverse impacts predicted. Likely to assist with aiming to achieve WFD compliance by 2015. No adverse impacts predicted. Likely to assist with aiming to achieve WFD compliance by 2015. No adverse impacts with a mining to achieve WFD compliance by 2015. No adverse impacts with a mining to achieve WFD compliance by 2015. No adverse impacts with a mining to achieve WFD compliance by 2015. No adverse impacts with a mining to achieve WFD compliance by 2015. No adverse impact with a mining to achieve WFD compliance by 2015. No adverse impacts with a mining to achieve WFD compliance by 2015. No adverse impacts with a mining to achieve WFD compliance by 2015. No adverse impacts with a mining to achieve WFD compliance by 2015. No adverse impacts with a mining to achieve WFD compliance by 2015. No adverse impacts with a mining to achieve WFD compliance by 2015. No adverse impacts with a may incur costs. Note and with a moverall suite and residents an	Do Nothing	Zero	Zero	for an obvious	compliance with WFD water quality target post- 2015. Likely on-going deterioration in	on-going deterioration of	Zero	Zero	option but unlikely to halt or reverse site condition
Nutrient remove 90% of lnigh – but may assuming high adverse from adding the water column, and claimed to lock up sediment P for up to 10 years. Nutrient remove 90% of high – but may assuming high adverse from adding the water column, and claimed to lock up sediment P for up to 10 years. Nutrient remove 90% of high – but may assuming high adverse from adding the properties of the concentration of foreign and claimed to lock up sediment P for up to 10 years. Nutrient remove 90% of high – but may assuming high adverse from adding the properties of the concentration of foreign and treated. Nutrient remove 90% of high – but may assuming high adverse from adding the properties of the prop		point sources (Sites 9 & 10). Less effective (moderate) for diffuse sources but can reduce diffuse sediment source 'hot	but an important component in an overall suite	>1 - 5 years	improvements in water quality. No adverse impacts predicted. Likely to assist with aiming to achieve WFD	wider community if early engagement sought. Potentially adverse response from landowners/resi dents affected by improvement notices/enforce	Landowners and residents	monitoring &	Natural England and Environment Agency already acting to rectify point source inputs to the
	Nutrient	remove 90% of OP from the water column, and claimed to lock up sediment P for	high – but may require frequent	assuming high concentration of OP is taken up quickly and sediment P is locked up	adverse from addition of foreign materials into a natural environment with nature conservation designations. Could assist with aiming to achieve WFD compliance by	adding chemicals to a natural lake. Beneficial impact from rapid response to treatment. Stakeholder acceptance could be compromised if viewed as a sticking plaster option rather than tackling	high depending on sediment depth treated. ~£50k per 0.1 m of sediment depth treated in the Inner basin. >£200k per 0.5 m of sediment depth treated in the	application may be required every 3 – 10	high cost, repeated applications and experimental nature of this approach result in low




Management Option	Nutrient Reduction Effectiveness	Probability of Success	Speed of Ecosystem Response	Environmental Impact	Community/ Social Impact	CAPEX	OPEX	Sustainability
Bio- manipulation	Variable and difficult to accurately predict.	Low to moderate, requires continual management.	>2 - 5 years.	Environmentall y benign unless non-native zebra mussels are introduced.	May receive community support as a low-impact option.	Moderate, to account for purchase of fish stock	Moderate – will require annual monitoring, management and possible replenishment of fish stocks	Moderate cost, uncertainty regarding nutrient reduction effectiveness, and likely low probability of success reduces the sustainability of this option.
Sediment Removal	Variable – some projects are highly successful while others are not. Difficult to determine factors for success and thus predict outcomes.	Moderate, but some evidence suggests that sediment nutrient concentrations can rapidly return to predredging levels.	>1 – 3 years.	Adverse impacts include damaging the lake lining, sediment disturbance, construction of large dewatering lagoons, sediment disposal to landfill, nutrient leakage. Potential short term adverse impacts to habitats, protected species, and SSSI values. Could assist with aiming to achieve WFD compliance.	Potential difficulty with sludge dewatering, reuse or disposal options. Potentially adverse aesthetics of dredging activity. Impacts to habitats, protected species and SSSI issues.	>£100k for 2,000 m³ of high-P sediment in the Inner basin. >£1M and >£2M for removal of 1 m depth throughout Inner and Middle basins respectively. Sediment dewatering costs to be determined. Sediment disposal to landfill - estimated cost approximately £120/tonne.	Zero (but may require subsequent dredging as sediment once again accumulates over time)	Potentially sustainable if successful but likely high carbon cost for sediment dewatering and disposal, plus adverse impacts (including to SSSI and adjacent land) reduce the sustainability of this option.
Inflow Re- configuration	High to very high depending on flushing rate.	High to very high.	>1 - 3 years assuming thermal stratification and sediment nutrient release prevented or minimised immediately.	Likely to assist with aiming to achieve WFD compliance. Potential impact of flushing nutrients to Outer basin (compromising	Restoring natural flow regime to Middle basin likely to be received positively. Increasing flushing of	Very high (>£500k) depending on extent of assessment & engineering required.	Low	A high cost but sustainable long-term option if impacts to Windermere are not significant.





Transfer Pipeline



Transfers clean well-oxygenated water from Great Langdale beck into the Inner basin of Elterwater.

Temporary abstraction licence.

Installed in Jan 2016.

Paleochannel reconnections



Little Langdale Beck

Channel diverted in 1850s









Channel reconnected in 2016






Figure 3.2. Rainfall inundation map of the Elter Water fan zone.

Monitoring





Sampling programme:

- Pre-intervention fortnightly sampling across three basins
- Post intervention Monthly samples in inner basin and at outfall

Post-Intervention:


- Phosphorus monitoring
- Chlorophyll and turbidity monitoring
- Water quality parameter monitoring at depth
- Water level monitoring through transfer pipe
- Repeat sediment survey was undertaken in 2019.









Total Phosphorus





Chlorophyll- a – Middle of Inner Basin



Next Steps



- Installation of large woody debris into Great Langdale beck to aid connection of scrapes.
- Altering the hands off flow for the transfer pipe to extend the period we can abstract water, especially during summer months.
- On-going monitoring until 2025 and repeat sediment survey.

Review data and decommissioning of pipeline





THANK YOU ANY QUESTIONS?



Jayne Wilkinson: jayne@scrt.co.uk

www.scrt.co.uk